

## iQ700, Built-in compact oven with steam function, 60 x 45 cm, Stainless steel CS656GBS7B















#### Optional accessories

HZ915003 HZ66X650 HZ66X600 HZ664000 HZ638D18 HZ636000 HZ631070 HZ625071 HZ531010 Shorten your cooking time thanks to fast preheat and coolStart. And remote your oven from anywhere with Home Connect.

- ✓ fast preheat: reach the required baking temperature sooner; coolStart: no need to preheat the oven for deep frozen food.
- ✓ The full steam function: making it simple to cook healthy and delicious meals
- ✓ cookControl Plus: quaranteed success for numerous dishes.
- ✓ 4D hotAir: flexible choice of shelf.
- ✓ softMove: gentle opening and closing of the oven door.

#### Feature

#### **Technical Data**

Color / Material Front : Stainless steel

Construction type : Built-in Door opening : Drop down

Required niche size for installation (HxWxD): 450-455 x 560-568 x

550

Dimensions: 455 x 594 x 548

Dimensions of the packed product (HxWxD) (mm) :  $530 \times 660 \times 690$ 

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 34.043 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 150

EAN code: 4242003839294

Current (A): 16
Voltage (V): 220-240
Frequency (Hz): 50; 60
Plug type: no plug
Approval certificates: CE, VDE

Number of cavities (2010/30/EC) : 1

Usable volume (of cavity) - NEW (2010/30/EC) : 47

Energy efficiency rating : A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

0.61

Energy efficiency index (2010/30/EC): 81.3





# iQ700, Built-in compact oven with steam function, 60 x 45 cm, Stainless steel CS656GBS7B

#### Features

#### Design

- 3.7" TFT touchDisplay
- Drop down oven door, softClose, softOpen
- •
- Cavity inner surface: enamel anthracite
- Stainless steel control dial
- We recommend you to choose complementary products within IQ700, in order to assure an optimal design combination of your Built-In appliances.
- Control panel lock
- Automatic safety switch off
- Residual heat indicator
- Start button
- Door contact switch
- •
- Digital temperature display with proposal
- Actual temperature display
- Heating-up indicator
- •
- WLAN Home connect enabled
- cookControl Plus
- Electronic oven clock timer
- LED light, Light on/off when door opened/closed
- Tank empty indicator
- Integral cooling fan
- 3 shelf positions

#### Cleaning

- EcoClean Direct : ceiling, back panel, side liners
- ecoClean programme
- Full glass inner door

### Programmes/functions

- Compact steam oven with 13 main functions heating methods:
   4D hot air, hotairGentle, conventional top & bottom heating,
   Conventional heat Gentle, hot air grilling, full width grill, half width grill, Pizza setting, coolStart, bottom heat, low temperature cooking, keep warm, plate warming
- Additional functions:
- Descaling programme
- Drying function
- autom. boiling point detection
- .
- Fast preheat

#### Accessories

 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

#### Performance/technical information


- Energy efficiency rating (acc. EU Nr. 65/2014): A+
- Energy consumption per cycle in conventional mode: 0.73 kWh
- Energy consumption per cycle in fan-forced convection mode: 0.61 kWh
- Number of cavities: Main cavity
- Heat source: electrical
- Cavity volume: 47 litre capacity
- Temperature range 30 °C 250 °C

- Location of water tank: Outside cavity
- 1 I Water tank capacity:
- Power cord length 150 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 594 mm x 548 mm
- Please refer to the dimensions provided in the installation manual



# iQ700, Built-in compact oven with steam function, 60 x 45 cm, Stainless steel CS656GBS7B

## Dimensioned drawings



If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	42 mm	43 mm
Full surface Induction hob	52 mm	53 mm
Gas hob	32 mm	43 mm
Electric hob	32 mm	35 mm

